

# Mechanical Fixture Kit


## MFS-D2 SERIES

The new single well MTest Solutions Mechanical Test Fixture (MFS), complies to most demanding In-Circuit and Functional Testing Challenges.

Interface plate cover is placed on back of Fixture, which can be freely customized according customer's requirements.

Due to its robust design this Fixture can easily handle up to 1000 Test Points\* without bending problems!

Equip **ND-MFS-D2-EXCH-PYL** Mechanical Fixture




Equip **ND-EXCH-D2-PYL**  
Exchangeable Kit with  
Pylon Interface

### Technical Features:

- External Dimension (width x deep x height) with Handles:  
409 mm x 567 mm x 280 mm  
[16.102 in x 22.323 in x 11.024 in]
- Usable Area: 133 mm x 218 mm [5.236 in x 8.583 in]
- Big inner space for Optional Hardware
- Ergonomic Handle for easy closing
- Exchangeable Kit is prepared with Pylon Interface Blocks
- ESD Safe & Easy Maintenance
- Quick Exchange System - Modular Fixture
- Alum-A-Grip Handles for transport and lift

### Optional Hardware for Fixture Customizing:

- Reed Relay Switch used as cover close sensor
- MU S001 D2 M12 x 1 PCB Engraving Unit
- CEM-1 Assembly Plate to Fixture housing bottom
- Digital Test Cycle Counter
- Safety Switch for High-Voltage Test
- Inductive Sensor to check Handle Position  
(to control actuation of safety switch)
- Pneumatic or Solenoid Cover Lock set



Engraving Unit

170 Pole Pylon Block

\*If standard 2 N Test Probes are used

